


Elcometer 3238 Long Edge Wet Film Combs



Elcometer 3238 Long Edge Wet Film Combs

Elcometer 3238 Long Edge Wet Film Combs

Similar to the Elcometer 115, the Elcometer 3238 provides the User with more measurement points (teeth). These rectangular wet film combs are available in 3 ranges - supplied either separately or in a set of 3.

Wet Film Thickness

It is important that a coating is applied to the correct thickness. Applying too much wet coating will not only waste and money, but also there is also a possibility of the coating cracking during the curing process. Too little coating and there is a chance that the substrate will not be sufficiently covered.

To control process variables, it is often desirable to measure whilst the film is still wet. Wet film measurements are also useful for systems where the dry film thickness can only be measured destructively.

At a glance

- *Stainless steel wet film combs with "teeth" along each long edge to provide more measurement points in on gauge.*
- *Available individually or in a pack of 3.*

Test Method - How to use a Wet Film Comb

Place a comb perpendicular to, and touching the substrate. Hold the comb in position and wait a few seconds until the teeth are "wet." Remove the comb from the film.

The wet film thickness lies between the biggest value "coated" or "wet" tooth and the smallest value "uncoated" or "dry" tooth value.

Can be used in accordance with:	
ASTM D 4414-A	BS 3900-C5-7B
ISO 2808-7B	NF T30-125

Model	Description	Range (µm)	Measurement Steps (µm)	Part Number
Elcometer 3238/1	Elcometer 3238 Long Edge Wet Film Comb	5 - 120	5	K0003238M001
Elcometer 3238/2	Elcometer 3238 Long Edge Wet Film Comb	25 - 600	25	K0003238M002
Elcometer 3238/3	Elcometer 3238 Long Edge Wet Film Comb	50 - 1200	50	K0003238M003
Elcometer 3238/4	Set of 3 Long Edge Wet Film Comb (Scales 1, 2 and 3)			K0003238M004

Related products



Elcometer 115

These precision film combs, formed in stainless steel to be long-lasting and reusable, are supplied in Metric and Imperial values on the same comb. Four separate ranges of thicknesses are available up to a maximum thickness of 1270µm (50mils). Each comb has 10 measurements (or teeth) per comb.



Elcometer 112/3236

Precision formed in stainless steel to be long-lasting and reusable, these hexagonal wet film combs are supplied in a range of thicknesses and can measure up to a maximum thickness of 3000µm (120mils). This high upper value allows measurement of thick coatings which are difficult to test by other methods.



Elcometer 112AL

Being punched from Aluminium, the Elcometer 112AL is not as accurate as the high precision versions but it does provide a low cost alternative for measurement of wet film thickness.



Elcometer 154

Made from ABS plastic, the Elcometer 154 Wet Film Combs are designed to be used only once and kept as a record of wet film thickness measurement for your ISO or customer requirements. Both Metric and Imperial values are on the same comb, 50 to 800µm on one side, 2 to 32mils on the reverse.



Elcometer 3230

Formally known as the Elcometer 120, the Elcometer 3230 wet film wheel consists of three circles. The central circle is of smaller diameter and is eccentric of the two outer circles. By rolling the gauge through a wet coating, the centre disc eventually touches the film. This point on the scale indicates the thickness. Various measurement ranges from 0 to 25µm - 0 to 3000µm (0 to 1mil - 0 to 40mils) are available.

ENGLAND

Elcometer Instruments Ltd
Edge Lane
Manchester M43 6BU

Tel: +44 (0) 161 371 6000
Fax: +44 (0) 161 371 6010
e-mail: sales@elcometer.com
www.elcometer.com

USA

Elcometer Instruments Inc
1893 Rochester Industrial Drive
Rochester Hills Michigan 48309

Tel: +1 248 650 0500
Toll free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com
www.elcometer.com

CANADA

Elcometer Canada Ltd
PO Box 622, 401 Ouelette Avenue
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: ca_info@elcometer.com
www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
896 Dunearn Rd
Sime Darby Centre #3-09
Singapore 589472,
Republic of Singapore

Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com
www.elcometer.com

BELGIUM

Elcometer SPRL
Rue Vallée 13
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.be
www.elcometer.be

FRANCE

Elcometer SARL
BP 8-Bou
60 Rue de la Petite Levée
45430 Chécy

Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.fr
www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
Himmlingstraße 18
D-73434 Aalen

Tel: +49 (0) 7366 91 92 83
Fax: +49 (0) 7366 91 92 86
e-mail: de_info@elcometer.de
www.elcometer.de